

# CERTIFICATE OF COMPLIANCE

**Certificate Number** R26797  
**Report Reference** R26797-20111206  
**Issue Date** 2020-SEPTEMBER-14

**Issued to:** SALTO SYSTEMS S L  
POL. LANBARREN. ARKOTZ 9  
20180 OIARTZUN SPAIN

**This certificate confirms that  
representative samples of**

ELECTRICALLY CONTROLLED SINGLE-POINT LOCKS  
AND LATCHES

See Addendum for models

Have been investigated by UL in accordance with the  
Standard(s) indicated on this Certificate.

**Standard(s) for Safety:**

ANSI/UL 10C, Positive Pressure of Fire Tests of Door  
Assemblies.

ANSI/UL 10B, Fire Tests of Door Assemblies.

CAN/ULC-S104-15, Standard Method for Fire Tests of Door  
Assemblies.


**Additional Information:**

See the UL Online Certifications Directory at  
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** R26797  
**Report Reference** R26797-20111206  
**Issue Date** 2020-SEPTEMBER-14


This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Salto LC1K Series with door position switch RFDTCTxx and Ai6 Series escutcheon electrically controlled single point lock sets of the cylindrical type. Model No. Salto LA1T Series mortise with door position switch RFDTCTxx and Ai6 or E16 Series escutcheon electrically controlled single point lock sets of the mortise type. These lock sets may be provided with 1/2 in. (13 mm) latchbolt for cylindrical type locks or 3/4 in. (19 mm) latchbolt for mortise type locks and a 2 3/8 in. (60 mm) or 2-3/4 in. (70 mm) backset. Models LA1T05, LA1T15, and LA1T35 use modified versions of mortise.

Model No. Salto LT2K Series with Ai6 Series or Ei6 Series escutcheon electrically controlled single point lock sets of the tubular type. These lock sets may be provided with 1/2 in. (13 mm) latchbolt for tubular type locks. For use on doors rated 45 minutes.

The Ai6 Series escutcheon include Model Nos. Ai650, Ai656, Ai658, Ai660, Ai666, and Ai668 and the Ei6 Series escutcheon include Model Nos. Ei650, Ei656, Ei658, Ei660, Ei666, and Ei668. The details of the escutcheon varied due to function capabilities of the lockset such as entry lock, privacy, room lock, key override, privacy with key override and hotel guest room lock with key override functions.

The model number of the lock is dependent upon the grade, backset, face plate size, finishes, function, and handling of levers.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

