

CERTIFICATE OF COMPLIANCE

Certificate Number 20140813- R38099
Report Reference R38099-20140731
Issue Date 2014-August-13


Issued to: SALTO SYSTEMS S L
POL. LANBARREN. ARKOTZ 9
20180 OIARTZUN SPAIN

**This is to certify that
representative samples of** FIRE-EXIT HARDWARE
See Addendum page

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: See Addendum page
Additional Information: See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Listing Mark for the US and Canada should be considered as being covered by UL's Listing and Follow-Up Service meeting the appropriate requirements for US and Canada.

The UL Listing Mark for the US and Canada generally includes: the UL in a circle symbol with "C" and "US" identifiers:  the word "LISTED"; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20140813- R38099
Report Reference R38099-20140731
Issue Date 2014-August-13

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Models/Products:

USL, CNL – Model No. PBF1100 with Ai6 Series escutcheon and KPB03 battery holder, fire exit hardware of the rim type.

..

Standard(s) for Safety

ANSI/UL 10C- Positive Pressure of Fire Tests of Door Assemblies.
ANSI/UL 10B- Fire Test for Door Assemblies
ANSI/UL 305- Standard for Safety Panic Hardware.
ANSI/BHMA A156.3-2008- American National Standard for Exit Devices
CAN/ULC-S132-07- Standard Method of Tests for Emergency Fire Exit Hardware
CAN/ULC S104- Standard Method for Fire Tests of Door Assemblies.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

