

SKG-IKOB PRODUCTCERTIFICATE

440.393.07

Date of issue: 29-01-2024



Certificate holder

Salto Systems SL
Poligono Lanbarren C / Arkotz 9
920180 Oiartzun
T: +34 (0) 943 344 550
E: info@saltosystems.com
I: www.saltosystems.com



Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

europofile cylinder with non lockable knob electro mechanical

delivered under logo / brand:

SALTO

delivered under type- and / or article number:

NME2xxG , NME2xxAG , NJE2xxG , NJE2xxAG

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A blue ink handwritten signature, appearing to be "H.A.J. van Dartel", written over a horizontal line.

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

CERTIFICATE

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

SKG-IKOB PRODUCTCERTIFICATE

Salto Systems SL
Number: 440.393.07

page 2 of 2

1. PRODUCT

europrofile cylinder with non lockable knob electro mechanical

PRODUCT TYPE

cylinder

2. TECHNICAL SPECIFICATION

Operating:	Mechanical and electrical operation
Construction:	Euro-profile cylinder double, with on both sides knob, 1 side lockable, with OR without panic function modulair double with on both sides a turning knob, 1 side lockable, with OR without panic function
System:	knob with full length plug, coupled with de cam by 1 side electronic operation operation by: - Keycard, Fob or Wearable - SALTO KS mobile app. on phone or tablet
Material:	cylinder body: brass with various coatings with OR without a steel bridge
Dimension:	17 mm profile from 30/30 mm in various extensions per 5 mm possibly with extended plug of +5 OR +10 mm
Fixing:	1 steel bolt M5, length \geq backset + 10 mm
Intended use:	The electromechanical product is operated electronically using the options stated under "System". The operating options listed below, as well as the closure, are included in the Self-declaration - additional product requirements for electromechanical and electronic hinges and locks; dated 08-01-2024, with which the certificate holder declares that the applicable requirements are met. in combination with cylinder mortice locks and security furniture. Pay Attention! This cylinder achieves only the SKG-star rating if a door element (including side window), wherein at least P4A glass has been applied, OR in a door element (including side window) with a section filling without a view on the knob. A wooden door element (including side window) with a view to the "standard" turning knob, should be provided with a SKG (V) certified anti-drill / manipulation device.

3. DELIVERY

The preconditions for correct installation and the fasteners to be used are described in the enclosed or digitally published installation instructions with the following version:

225790-ED.1 - 12-09-2023

225791-ED.1 - 12-09-2023

227823-ED0 - 23-05-2023

4. PERFORMANCES

A europrofile cylinder with non lockable knob electro mechanical according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this euro-profile cylinder with non lockable knob, electro mechanical is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 3 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this euro-profile cylinder with non lockable knob, electro mechanical is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).

SKG-IKOB PRODUCTCERTIFICATE

Salto Systems SL
Number: 440.393.07
